

Applications

The ABS Scaba agitators are individually tailored for all applications wherever a liquid is to be mixed with another liquid, particles or gas.

These agitators are used in wastewater applications, process industry and paper industry.

Design

The agitators are of a robust, modular design and can be combined with various types of drive units, seals and impellers. Due to this flexibility, the agitators can be adapted optimally to the need of the process.

Drive unit

The drive unit selected is determined by the process requirement and the customer's demands.

Pedestal module

The pedestal module is equipped with a double spherical roller bearing with adapter sleeve. For a V-belt drive and certain special applications, an extra shaft bearing is built into the pedestal module.

Housing for shaft seal

The housing for the shaft seal is equipped with a suitable seal. The connecting flange of the housing can be supplied in different sizes.

Motor

Power ratings: 0.12-250kW. The options are electric motors.

Shaft seal

The shaft seals are designed to maintain the required pressure in the tank or to prevent leakage through the shaft entry. Seals are also used to prevent impurities from entering the tank, or to prevent damage to the agitator by splashing or by vapour from the process liquid.

The shaft seals options are single or double mechanical seals, stuffing box, TH, TL and TS seals and labyrinth seal.



Properties

Propeller diameter:	100mm - 6m (4-236 inches)
Power up to:	250kW (335 hp)
Shaft length up to:	30m (100 ft)

Shaft coupling

The agitator is equipped with one or more shaft couplings, if necessary. The couplings are of flange type, although if the hygienic requirements are strict, threaded shaft couplings can be supplied instead.


Agitator impeller

Scaba has a wide range of patented agitator impellers which are selected to suit specific applications.

Combined with our extensive know-how, these impellers produce the best possible process results at the lowest possible energy costs.



Shaft seals



Mechanical seal

- Double or single design
- Dry or liquid lubricated
- Split seal
- Liquid-cooled seal housing
- Cartridge seal

Stuffing box seal

The lantern ring, usually included, serves as a gliding bearing and increases the useful life of the seal.

The shaft is often equipped with a wear sleeve.

- 5 packing plaits

TH seal

Hygienic seal designed to prevent the ingress of oil and impurities into the process liquid.

TL seal

Protects the agitator from splashing. Complete in PTFE without rubber details. Particularly suitable in areas with aggressive media where rubber details is inappropriate.

TS seal

Lip seal designed to prevent the ingress of impurities into the process liquid. Protects the agitator from splashing.

Labyrinth seal

Seal for low-pressure processes. Particularly suitable for digesters. The height of the water trap is determined by the pressure inside the tank.

- Can be equipped with level control in the labyrinth

Impellers



SHP1

Our high-flow propeller which is acknowledged for its energy-efficiency and effectiveness.

It is just as effective on difficult suspensions and reactions as it is on homogenizing and mixing. Intended for viscosities up to 50 000 mPas.

SHP18

A registered-design development of the SHP1.

Offers better effectiveness at lower viscosities. Low weight allows for lighter shaft design.

SHPD

Double-acting propeller for high viscosities, up to paste consistency. Also suitable for very gentle stirring. Due to the double-acting function, the liquid is pumped both downwards and upwards.

SRGT

Patented turbine intended for gas dispersion. Due to its design, the power demand is constant at varying gas flows. Performs very well also on three-phase systems comprising liquid - gas - particles.

Other agitator elements

Our range also includes impellers of conventional type.



We know how water works

| ABS Group, Roskildevägen 1, Box 394, SE-201 23 Malmö, Sweden | Tel +46 40 35 04 00 | Fax +46 40 30 50 45 |
| www.absgroup.com |

T 0294-457712 F 0294-457713 info@pompdirect.nl