



Mini

Electrical submersible drainage pump

POMPDIRECT


grindex
www.grindexpompen.nl


50 Hz	Mini
Discharge connection	2"
Rated power P_2 [W]	900
Max. power consumption P_1 [W]	1200
Shaft speed [r.p.m.]	2800
Rated current at 115V	11 A
Rated current at 230V	5,2 A
Solids passage [mm]	11 x 5
Height [mm]	440
Diameter [mm]	185
Weight [kg]	14,5
<i>Other voltages on request</i>	



ISO 9906/A

Pump types

Single phase

Classification

Electrical submersible drainage pump

Protection class: IP 68

Electrical motor

1-phase: Squirrel cage induction motor

50 Hz: separate start and run capacitor

60 Hz: combined start and run capacitor

Insulation class: F (IEC 85)

Motor protection

1-phase: Temperature guard with a thermal contact in stator opening temperature 135°C (275°F)

Cable1-phase: 3G1mm², 10 m (33 ft) / 16AWG/3, 50 ft**Limitations**

Max. submersion depth: 10 m (32.8 ft)

Max. liquid temperature: 40 °C (104 °F)

Allowed pH range: 5 - 8

Maximum liquid density: 1100 kg/m³ (68 lbs/ft³)**Shaft seals**

Double mechanical seals running in an oil compartment

Material lower seal: *silicon carbide - silicon carbide*Material upper seal: *carbon - aluminum oxide***Bearings**

Ball bearings with C3-clearance

Discharge connection

2" hose, BSP or NPSM

MaterialsPump top: *Aluminium*Outer casing: *Aluminium*Stator housing: *Aluminium*Motor shaft: *Stainless steel*Impeller: *Polyurethane*Diffuser: *Polyurethane*Screws and nuts: *Stainless steel***Accessories**

Float switch

Low suction collar

Pump raft

POMPDIRECT

T +31 (0)294-457712 F +31 (0)294-457713
www.grindexpompen.nl info@pompdirect.nl

Specifications can be changed without notice