

Pump type: Submersible pump
 Application: Waste water, sewage

Pump data

Solids passage: 100 mm
 Discharge/ Suction: NW100 /NW125, PN10
 Impeller type: closed screw
 Impeller diameter: 230 - 250 mm
 Recommended min. flow: 6 l/sec (21 m3/h)
 Weight: 153 kg





Motor

Mains: 50 c/s – 3 phase
 Rated shaft power: 13.0 kW
 Rated electrical power: 15.1 kW
 Nominal speed: 1420 rpm
 Motor efficiency: 86 %
 Power factor (cos phi): 0.84
 Degree of protection: IP 68
 Isolation class: F (155°C)
 Max. water temperature: 40°C
 Standard cable length: 10 m

Materials

Pump casing: Cast iron GG 25 (EN-GJL-250)
 Impeller: S.g cast iron GGG 40 (EN-GJS-400-15)
 Motor unit: Cast iron GG 25 (EN-GJL-250)
 Shaft: AISI 431
 Bolt: Alt: AISI 316
 Bolts: AISI 316
 Elastomers: Nitrile (NBR) or Neoprene (CR)
 Alt: Viton (FPM)
 Electrical cable: Neoprene (CR)
 Seal lubrication: Oil
 Seal pump side: Silicon carbide – Silicon carbide - FPM
 Seal motor side: Carbon – Ceramic - NBR
 Coating: Two components Polyurethane

Installation options

Header coupling: BWK 100 
 Guide bar coupling: OWK 100-N 
 Freestanding Including support (VRS): 100mm hose connection or G 4" threaded connection 
 Dry Installation Including cooling system (ODO): vertical or horizontal install. discharge flange NW100 suction flange NW125 

Optional

- Flameproof version, to class: II 2 G Ex d IIB c T4
 Standard: II 2 G Ex b c d IIB T4 Gb
 With Frequency control: II 2 G Ex b c d IIB T3 Gb
- Thermo switches in stator windings
- Cable protective sheathing (AISI 316)
- Water detector in motor and oil chamber

Connections

voltage [V]*	current [A]	Electrical cable size [mm2]		motor protection and/or water detector		flameproof version	
		direct start	stardelta start	direct start	stardelta start	direct start	stardelta start
230	45.4	4G10	2x4G6	4G10 + 4G1.5	-	4G10 + 4G2.5	-
400	26.1	4G6	7G2.5	4G6 + 4G1.5	7G2.5 + 4G1.5	4G6 + 4G2.5	7G2.5 + 4G2.5
500	20.9	4G6	7G1.5	4G6 + 4G1.5	12G1.5	4G6 + 4G2.5	12G1.5
starting current DOL start : 5.0 x rated current							
starting current YD start : 1.7x rated current							
							* other voltages on request

